

VTA-135-H



**Pick-Up Mounted
Telescopic Platform**

**Keeping you safe whilst
maximising productivity.**

VTA-135-H | PICK-UP MOUNTED

Technical Specifications

	Working Height	13.6m
	Platform Height	11.6m
	Outreach	6.4m
	Gross Vehicle Weight (GVW)	3500kg
	Payload*	555kg
	Bucket Capacity	230kg
	Flyboom	N/A
	Lift Rotation	370°
	Height	2500mm
	Length	5575mm
	Wheelbase	3125mm
	Slope Longitudinally	5°
	Slope Sideways	3°
	Outriggers	Double A-Frame

Technical information is subject to change without prior notice. *Depending on the vehicle and subject to options fitted. Max payload after driver, passenger and fuel subject to options fitted.

Standard Equipment

- Lightweight profiled boom
- Fully hydraulic proportional control
- 240kg SWL plastic walk-in bucket
- Zero tail-swing on knuckle
- Access to bucket when in dock or from ground
- 12V DC emergency lowering system
- Emergency manual hand pump
- Low travel height <2.6m
- On and off road
- Towing capability
- Euro 6 compliance
- National Small Series Type Approved (NSSTA) allowing fast delivery
- Two year warranty

Options and Accessories

- Duck under bucket
- LED lights
- Lockers
- Reverse camera
- Run lock
- Chevrons
- Versalift Repair & Maintenance packages

Vehicle Options



Contact us for full vehicle list.

Diagrams

